

job name:   
 type:

## Quick Ship tiki™ LED spec sheet

### Quick Ship

Need fixtures quick? Get up to 10 pieces of our tiki™ LED series in 10 business days or less. Need more than 10, contact your local Rep for our current lead times. Orders are Ground Freight Allowed.

### material

**housing**  
 two-piece precision CNC spun .063" aluminum. downlight housing with rolled bottom edge for added strength. inverted bell upright element.

**downlight array platform**  
 .080" spun aluminum.

### optics

.050" spun aluminum conical reflector finished in high reflectance (>92%) matte white powder coat, for downlight. COB for indirect light is covered by LEDIL zorya lens for wide distribution.

### LED

COB arrays in 3500K (80 cri). under normal operating conditions, the LEDs employed are rated for >55,000hrs L70 (6.8K) per IES TM-21 from LM-80 test data, and 200,000hrs L70 projected life. Dual Distribution Direct/Indirect standard on Quick Ship tiki. white power cord is standard.

### drivers

integral, class P programmable, class A sound rating, universal input (120-277 vac), 1% minimum dimming level, PF >90, THD <20% at full load, open/short circuit protection. input/output isolation, surge protection (3KV), wired for 0-10v dimming from factory. Two drivers operate dual distribution direct/indirect.

### mounting

5"dia. spun steel canopy in satin white with 6ft stainless steel cable tripod and field adjustable grippers that allow for exact AFF mounting heights.

### finish

silver anodized finish.

### emergency

if required, recommend use of inverter (by other).



## catalog number

<b>QSP5113</b>	<b>35K</b>	<b>AN</b>
<b>size</b> QSP5113 13"dia X 16.25"ht	<b>LED array</b> 35K 3500K	<b>powerhead finish</b> AN silver anodized

Cat No	Direct Delivered Lumens		Watts		Amps		Indirect Delivered Lumens*		Watts		Amps	
	120V	277V	120V	277V	120V	277V	120V	277V	120V	277V	120V	277V
<b>QSP5113 HI</b>		46	.38	.17		29	.24	.10				
3500K	3127				1952							

