

job name:
 type:

6"/12" sq.too™ spec sheet 90CRI

material

2" smooth square extruded architectural 6063 aluminum outer housing in six lengths. satin black canopy and stem standard on wood finishes.

LED

COB in 2700K, 3000K, 3500K, or 4000K 90+ cri standard rated >36,000 hours L70 (6.8K) per LM-80 test data, and 71,000 hours projected life per IES TM-21.

downlight optics

Khatod® Cosmo 50mm dia 16mm high (RoHS compliant) available in 12° spot, 25° medium, 38° wide

driver

constant current, class P, class 2 power unit, class A sound rating, universal input (120-277V) programmable driver, 5% minimum dimming level, PF >0.90. protections include short circuit, input/output isolation and surge protection (3KV). wired for 0-10v dimming from factory.

mounting

standard

driver in junction box (requires 2 1/8" deep electrical box). 5"sq canopy painted to match fixture. rigid mount 3/8"dia stem standard. painted to match fixture. satin black canopy and stem standard on wood finishes.

canopy mounted driver (CDVR) (optional)

2"sq x 6"h extruded aluminum driver housing on 5"sq canopy painted to match fixture. rigid mount 3/8"dia stem standard. painted to match fixture.

remote enclosure (.LV) (optional)

the standard driver can be remote mounted up to 33ft from the LED. suspension length should be considered in distance. remote enclosure supplied. for distances greater than 33ft consult factory. for Chicago Plenum installation consult factory.

finish

select from 15 standard powder coat paint finishes or 3 wood finishes (listed below) or specify RAL# for custom colors. satin black canopy and stem standard on wood finishes.

emergency

if required, recommend use of inverter (by other).



catalog number

| | | | | | |
|--|--|--|--|--|--|
| | | | | | |
|--|--|--|--|--|--|

| size | beam | CCT | lumens | painting finish | options |
|--|----------------------------|-------------------|----------------------|--------------------------|-----------------------------------|
| P4006 driver in j-box | S 12° spot | 27 2700K | L1 360 lm | AP anodized paint | STM1 12" stem |
| P4006.BABA driver in j-box | M 25° med | 30 3000K | L2 630 lm | BS brass | STM2 24" stem |
| P4006.LV remote enclosure 2"sq X 6"ht | W 38° wide | 35 3500K | L3 900 lm | BU blue | STM3 36" stem |
| P4012 driver in j-box | jewel see page 6 | 40 4000K | H1 1265 lm | BZ bronze | CDVR canopy mounted driver |
| P4012.BABA driver in j-box | | H2 1805 lm | CP champagne | | |
| P4012.LV remote enclosure 2"sq X 12"ht | | | FB flat black | | |
| | | | | GM gun metal | |
| | | | | MB military blue | |
| | | | | MW matte white | |
| | | | | OR orange | |
| | | | | RD red | |
| | | | | SB satin black | |
| | | | | SS satin silver | |
| | | | | TG textured gray | |
| | | | | YO yellow | |



premium finish

RAL specify RAL#

wood finish

- ASH** ashwood
- ENG** english brown oak
- ESP** espresso

satin black canopy and stem standard on wood finishes

This product meets the guidelines for the Build America, Buy America Act. Some Exclusions Apply. For more information and full list of eligible SKUs, please contact the factory at info@impactitg.com

job name:
 type:

18"/24" sq.too™ spec sheet 90CRI

material
 2" smooth square extruded architectural 6063 aluminum outer housing in six lengths. satin black canopy and stem standard on wood finishes.

LED
 COB in 2700K, 3000K, 3500K, or 4000K 90+ cri standard rated >36,000 hours L70 (6.8K) per LM-80 test data, and 71,000 hours projected life per IES TM-21.

downlight optics
 Khatod® Cosmo 50mm dia 16mm high (RoHS compliant) available in 12° spot, 25° medium, 38° wide

driver
 constant current, class P, class 2 power unit, class A sound rating, universal input (120-277V) programmable driver, 5% minimum dimming level, PF >0.90. protections include short circuit, input/output isolation and surge protection (3KV). wired for 0-10v dimming from factory.


mounting standard
 driver in junction box (requires 2 1/8" deep electrical box). 5"sq canopy painted to match fixture. rigid mount 3/8"dia stem standard. painted to match fixture. satin black canopy and stem standard on wood finishes.

canopy mounted driver (CDVR) (optional)
 2"sq x 6"h extruded aluminum driver housing on 5"sq canopy painted to match fixture. rigid mount 3/8"dia stem standard. painted to match fixture.

remote enclosure (.LV) (optional)
 the standard driver can be remote mounted up to 33ft from the LED. suspension length should be considered in distance. remote enclosure supplied. for distances greater than 33ft consult factory. for Chicago Plenum installation consult factory.

finish
 select from 15 standard powder coat paint finishes or 3 wood finishes (listed below) or specify RAL# for custom colors. satin black canopy and stem standard on wood finishes.

emergency
 if required, recommend use of inverter (by other).



catalog number

| | | | | | |
|--|--|--|--|--|--|
| | | | | | |
|--|--|--|--|--|--|

| size | beam | CCT | lumens | finished | options |
|--|----------------------------|-----------------|-------------------|--------------------------|-----------------------------------|
| P4018 driver in j-box | S 12° spot | 27 2700K | L1 360 lm | AP anodized paint | STM1 12" stem |
| P4018.BABA driver in j-box | M 25° med | 30 3000K | L2 630 lm | BS brass | STM2 24" stem |
| P4018.LV remote enclosure 2"sq X 18"ht | W 38° wide | 35 3500K | L3 900 lm | BU blue | STM3 36" stem |
| P4024 driver in j-box | jewel see page 6 | 40 4000K | H1 1265 lm | BZ bronze | CDVR canopy mounted driver |
| P4024.BABA driver in j-box | | | H2 1805 lm | CP champagne | |
| P4024.LV remote enclosure | | | | FB flat black | |
| P4024.LV.BABA* remote enclosure 2"sq X 24"ht | | | | GM gun metal | |
| | | | | MB military blue | |
| | | | | MW matte white | |
| | | | | OR orange | |
| | | | | RD red | |
| | | | | SB satin black | |
| | | | | SS satin silver | |
| | | | | TG textured gray | |
| | | | | YO yellow | |



premium finish
 RAL specify RAL#

wood finish
ASH ashwood
ENG english brown oak
ESP espresso
 satin black canopy and stem standard on wood finishes



This product meets the guidelines for the Build America, Buy America Act. Some Exclusions Apply. For more information and full list of eligible SKUs, please contact the factory at info@impactitg.com

job name:
 type:

36"/48" sq.too™ spec sheet 90CRI

material

2" smooth square extruded architectural 6063 aluminum outer housing in six lengths. satin black canopy and stem standard on wood finishes.

LED

COB in 2700K, 3000K, 3500K, or 4000K 90+ cri standard rated >36,000 hours L70 (6.8K) per LM-80 test data, and 71,000 hours projected life per IES TM-21.

downlight optics

Khatod® Cosmo 50mm dia 16mm high (RoHS compliant) available in 12° spot, 25° medium, 38° wide

driver

constant current, class P, class 2 power unit, class A sound rating, universal input (120-277V) programmable driver, 5% minimum dimming level, PF >0.90. protections include short circuit, input/output isolation and surge protection (3KV). wired for 0-10v dimming from factory.

mounting

standard

driver in junction box (requires 2 1/8" deep electrical box). 5"sq canopy painted to match fixture. rigid mount 3/8"dia stem standard. painted to match fixture. satin black canopy and stem standard on wood finishes.

canopy mounted driver (CDVR) (optional)

2"sq x 6"h extruded aluminum driver housing on 5"sq canopy painted to match fixture. rigid mount 3/8"dia stem standard. painted to match fixture.

remote enclosure (.LV) (optional)


the standard driver can be remote mounted up to 33ft from the LED. suspension length should be considered in distance. remote enclosure supplied. for distances greater than 33ft consult factory. for Chicago Plenum installation consult factory.

finish

select from 15 standard powder coat paint finishes or 3 wood finishes (listed below) or specify RAL# for custom colors. satin black canopy and stem standard on wood finishes.

emergency

if required, recommend use of inverter (by other).



catalog number

| | | | | | |
|--|--|--|--|--|--|
| | | | | | |
|--|--|--|--|--|--|

| size | beam | CCT | lumens | painting finish | options |
|--|----------------------------|-----------------|-------------------|--|-----------------------------------|
| P4036* driver in j-box | S 12° spot | 27 2700K | L1 360 lm | AP anodized paint | STM1 12" stem |
| P4036.BABA* driver in j-box | M 25° med | 30 3000K | L2 630 lm | BS brass | STM2 24" stem |
| P4036.LV* remote enclosure | W 38° wide | 35 3500K | L3 900 lm | BU blue | STM3 36" stem |
| P4036.LV.BABA* remote enclosure | jewel see page 6 | 40 4000K | H1 1265 lm | BZ bronze | CDVR canopy mounted driver |
| 2"sq X 36"ht | | | H2 1805 lm | CP champagne | |
| P4048* driver in j-box | | | | FB flat black | |
| P4048.BABA* driver in j-box | | | | GM gun metal | |
| P4048.LV* remote enclosure | | | | MB military blue | |
| P4048.LV.BABA* remote enclosure | | | | MW matte white | |
| 2"sq X 48"ht | | | | OR orange | |
| | | | | RD red | |
| | | | | SB satin black | |
| | | | | SS satin silver | |
| | | | | TG textured gray | |
| | | | | YO yellow | |
| | | | | premium finish RAL specify RAL# | |
| | | | | wood finish | |
| | | | | ASH ashwood | |
| | | | | ENG english brown oak | |
| | | | | ESP espresso | |
| | | | | satin black canopy and stem standard on wood finishes | |






*extended lead time

remote enclosure

This product meets the guidelines for the Build America, Buy America Act. Some Exclusions Apply. For more information and full list of eligible SKUs, please contact the factory at info@impactitg.com





Calculation Table

Consult factory for applications assistance




| Cat No | Delivered* Lumens | Watts 120V / 277V | IES File # | LLF to be applied |
|-----------|-------------------|-------------------|--------------------|-------------------|
| L1 | 360 | 3 | 07222C spot | .30 |
| | | | 07222B med | .30 |
| | | | 07222A wide | .30 |
| L2 | 630 | 6 | 07222C spot | .53 |
| | | | 07222B med | .53 |
| | | | 07222A wide | .53 |
| L3 | 900 | 9 | 07222C spot | .76 |
| | | | 07222B med | .76 |
| | | | 07222A wide | .76 |
| H1 | 1265 | 13 | 07222C spot | 1.07 |
| | | | 07222B med | 1.07 |
| | | | 07222A wide | 1.07 |
| H2 | 1805 | 19 | 07222C spot | 1.52 |
| | | | 07222B med | 1.52 |
| | | | 07222A wide | 1.52 |


*delivered lumens based on 4000K, 90+ cri

The application of a Light Loss Factor is required to:


- match the lumen output for the power module specified
- incorporate the increased lumen output due to LED/Driver upgrades



07222C
P40xx-S-40H1
S 12° spot



07222B
P40xx-M-40H1
M 25° med



07222A
P40xx-W-40H1
W 38° wide

job name:
 type:

sq.too™ with jewel spec sheet 90CRI

material

2"dia smooth extruded aluminum outer housing in six lengths. satin black canopy and stem standard on wood finishes.

LED

COB in 2700K, 3000K, 3500K, or 4000K 90+ cri standard rated >36,000 hours L70 (6.8K) per LM-80 test data, and 71,000 hours projected life per IES TM-21.

jewel

3D printed with filament. available in black, frost, and blue.

driver

constant current, class P, class 2 power unit, class A sound rating, universal input (120-277V) programmable driver, 5% minimum dimming level, PF >0.90. protections include short circuit, input/output isolation and surge protection (3KV). wired for 0-10v dimming from factory.

mounting

standard

driver in junction box (requires 2 1/8" deep electrical box). 5" dia canopy painted to match fixture. cloth-covered power cord color options listed below. cloth cord requires special stripping tool (link). field-adjustable 3ft length. optional stem listed below, painted to match fixture. satin black canopy and stem standard on wood finishes.

canopy mounted driver (CDVR) (optional)

2"dia x 6"h extruded aluminum driver housing on 5" dia canopy painted to match fixture. field-adjustable 3ft length. optional stem listed below, painted to match fixture.

remote enclosure (.LV) (optional)

the standard driver can be remote mounted up to 33ft from the LED. suspension length should be considered in distance. remote enclosure supplied. for distances greater than 33ft consult factory. for Chicago Plenum installation consult factory.

finish

select from 15 standard powder coat paint finishes or 3 wood finishes (listed below) or specify RAL# for custom colors. satin black canopy and stem standard on wood finishes.

emergency

if required, recommend use of inverter (by other).




catalog number

| | | | | | | |
|--|--|--|--|--|--|--|
| | | | | | | |
|--|--|--|--|--|--|--|

| size | jewel | length | CCT | lumens | finished | options |
|--|---|---------------------|-----------------|-----------------|--|---|
| P4006 driver in j-box | DBK black | 2 2" | 27 2700K | L1 | AP anodized paint | STM1 12" stem |
| P4006.BABA driver in j-box | diamond | | | | | STM2 24" stem |
| P4006.LV remote enclosure 2"sq X 6"ht | PFR frost pinstripe | | 30 3000K | L2 | | STM3 36" stem |
| P4012 driver in j-box | KBL blue knurled | | 35 3500K | L3 | BS brass BU blue BZ bronze CP champagne FB flat black GM gun metal MB military blue MW matte white OR orange RD red SB satin black SS satin silver TG textured gray YO yellow | CDVR canopy mounted driver |
| P4012.BABA driver in j-box | | | 40 4000K | contact factory | | |
| P4012.LV remote enclosure 2"sq X 12"ht | | | | | | |
| P4018 driver in j-box | | | | | premium finish RAL specify RAL# |  |
| P4018.BABA driver in j-box | | | | | | |
| P4018.LV remote enclosure 2"sq X 18"ht | | | | | | |
| P4024 driver in j-box | | | | | wood finish ASH ashwood ENG english brown oak ESP espresso satin black canopy and stem standard on wood finishes | |
| P4024.BABA driver in j-box | | | | | | |
| P4024.LV remote enclosure P4024.LV.BABA* remote enclosure 2"sq X 24"ht | | | | | | |
| P4036* driver in j-box | | | | | | |
| P4036.BABA* driver in j-box | | | | | | |
| P4036.LV* remote enclosure | | | | | | |
| P4036.LV.BABA* remote enclosure 2"sq X 36"ht |  | | | | | |
| P4048* driver in j-box | | | | | | |
| P4048.BABA* driver in j-box | | | | | | |
| P4048.LV* remote enclosure | | | | | | |
| P4048.LV.BABA* remote enclosure 2"sq X 24"ht | | *extended lead time | | | | |

This product meets the guidelines for the Build America, Buy America Act. Some Exclusions Apply. For more information and full list of eligible SKUs, please contact the factory at info@impactltg.com

Powder Coat Paint Finishes



MW matte white




AP anodized paint



SS satin silver



TG textured gray



FB flat black



SB satin black



CP champagne



BZ bronze



GM gun metal



OR orange 2011



BU blue 5017



BS brass



RD red 3020



YO yellow 1018



MB military blue

Premium Finishes*

Wood Finishes



ASH ashwood



ENG english brown oak



ESP espresso

For accurate color verification, actual finish samples are available upon request.



RAL#

*Available on select series. Consult product submittal for availability.

