

job name:   
 type:

## 6"/12" sq.too™ ceiling spec sheet 90CRI

### material

2" smooth square extruded architectural 6063 aluminum outer housing in six lengths. satin black canopy standard on wood finishes.

### LED

COB in 2700K, 3000K, 3500K, or 4000K 90+ cri standard rated >36,000 hours L70 (6.8K) per LM-80 test data, and 71,000 hours projected life per IES TM-21.

### downlight optics

Khatod® Cosmo 50mm dia 16mm high (RoHS compliant) available in 12° spot, 25° medium, 38° wide

### driver

constant current, class P, class 2 power unit, class A sound rating, universal input (120-277V) programmable driver, 5% minimum dimming level, PF >0.90. protections include short circuit, input/output isolation and surge protection (3KV). wired for 0-10v dimming from factory.

### mounting

#### standard

driver in junction box (requires 2 1/8" deep electrical box). 5"sq canopy painted to match fixture. satin black canopy standard on wood finishes.

#### remote enclosure (.LV) (optional)


the standard driver can be remote mounted up to 33ft from the LED. suspension length should be considered in distance. remote enclosure supplied. for distances greater than 33ft consult factory. for Chicago Plenum installation consult factory.

### finish

select from 15 standard powder coat paint finishes or 3 wood finishes (listed below) or specify RAL# for custom colors. satin black canopy standard on wood finishes.

### emergency

if required, recommend use of inverter (by other).



## catalog number

--	--	--	--	--

### size

**C4006** driver in j-box  
**C4006.LV** remote enclosure  
 2"sq X 6.25"ht

**C4012** driver in j-box  
**C4012.BABA** driver in j-box  
**C4012.LV** remote enclosure  
 2"sq X 12.25"ht

### beam

**S** 12° spot  
**M** 25° med  
**W** 38° wide

**jewel**  
 see page 6

### CCT

**27** 2700K  
**30** 3000K  
**35** 3500K  
**40** 4000K

### lumens

**L1** 360 lm  
**L2** 630 lm  
**L3** 900 lm  
**H1** 1265 lm  
**H2** 1805 lm

### painted finish

**AP** anodized paint  
**BS** brass  
**BU** blue  
**BZ** bronze  
**CP** champagne  
**FB** flat black  
**GM** gun metal  
**MB** military blue  
**MW** matte white  
**OR** orange  
**RD** red  
**SB** satin black  
**SS** satin silver  
**TG** textured gray  
**YO** yellow

### premium finish

**RAL** specify RAL#

### wood finish

**ASH** ashwood  
**ENG** english brown oak  
**ESP** espresso  
 satin black canopy standard on wood finishes



remote enclosure

This product meets the guidelines for the Build America, Buy America Act. Some Exclusions Apply. For more information and full list of eligible SKUs, please contact the factory at info@impactitg.com

job name:   
 type:

# 18"/24" sq.too™ ceiling spec sheet 90CRI

**material**  
 2" smooth square extruded architectural 6063 aluminum outer housing in six lengths. satin black canopy standard on wood finishes.

**LED**  
 COB in 2700K, 3000K, 3500K, or 4000K 90+ cri standard rated >36,000 hours L70 (6.8K) per LM-80 test data, and 71,000 hours projected life per IES TM-21.

**downlight optics**  
 Khatod® Cosmo 50mm dia 16mm high (RoHS compliant) available in 12° spot, 25° medium, 38° wide

**driver**  
 constant current, class P, class 2 power unit, class A sound rating, universal input (120-277V) programmable driver, 5% minimum dimming level, PF >0.90. protections include short circuit, input/output isolation and surge protection (3KV). wired for 0-10v dimming from factory.

**mounting standard**  
 driver in junction box (requires 2 1/8" deep electrical box). 5"sq canopy painted to match fixture. satin black canopy standard on wood finishes.

**remote enclosure (.LV)** (optional)  
 the standard driver can be remote mounted up to 33ft from the LED. suspension length should be considered in distance. remote enclosure supplied. for distances greater than 33ft consult factory. for Chicago Plenum installation consult factory.

**finish**  
 select from 15 standard powder coat paint finishes or 3 wood finishes (listed below) or specify RAL# for custom colors. satin black canopy standard on wood finishes.

**emergency**  
 if required, recommend use of inverter (by other).



## catalog number

--	--	--	--	--

**size**  
**C4018** driver in j-box  
**C4018.BABA** driver in j-box  
**C4018.LV** remote enclosure  
 2"sq X 18.25"ht  
  
**C4024** driver in j-box  
**C4024.BABA** driver in j-box  
**C4024.LV** remote enclosure  
 2"sq X 24.25"ht

**beam**  
**S** 12° spot  
**M** 25° med  
**W** 38° wide  
  
**jewel**  
 see page 6

**CCT**  
**27** 2700K  
**30** 3000K  
**35** 3500K  
**40** 4000K

**lumens**  
**L1** 360 lm  
**L2** 630 lm  
**L3** 900 lm  
**H1** 1265 lm  
**H2** 1805 lm

**painted finish**  
**AP** anodized paint  
**BS** brass  
**BU** blue  
**BZ** bronze  
**CP** champagne  
**FB** flat black  
**GM** gun metal  
**MB** military blue  
**MW** matte white  
**OR** orange  
**RD** red  
**SB** satin black  
**SS** satin silver  
**TG** textured gray  
**YO** yellow

**premium finish**  
**RAL** specify RAL#

**wood finish**  
**ASH** ashwood  
**ENG** english brown oak  
**ESP** espresso  
 satin black canopy standard on wood finishes



remote enclosure

This product meets the guidelines for the Build America, Buy America Act. Some Exclusions Apply. For more information and full list of eligible SKUs, please contact the factory at info@impactitg.com



job name:   
 type:

## 36"/48" sq.too™ ceiling spec sheet 90CRI

### material

2" smooth square extruded architectural 6063 aluminum outer housing in six lengths. satin black canopy standard on wood finishes.

### LED

COB in 2700K, 3000K, 3500K, or 4000K 90+ cri standard rated >36,000 hours L70 (6.8K) per LM-80 test data, and 71,000 hours projected life per IES TM-21.

### downlight optics

Khatod® Cosmo 50mm dia 16mm high (RoHS compliant) available in 12° spot, 25° medium, 38° wide

### driver

constant current, class P, class 2 power unit, class A sound rating, universal input (120-277V) programmable driver, 5% minimum dimming level, PF >0.90. protections include short circuit, input/output isolation and surge protection (3KV). wired for 0-10v dimming from factory.

### mounting

#### standard

driver in junction box (requires 2 1/8" deep electrical box). 5"sq canopy painted to match fixture. satin black canopy standard on wood finishes.

#### remote enclosure (.LV) (optional)

the standard driver can be remote mounted up to 33ft from the LED. suspension length should be considered in distance. remote enclosure supplied. for distances greater than 33ft consult factory. for Chicago Plenum installation consult factory.

### finish

select from 15 standard powder coat paint finishes or 3 wood finishes (listed below) or specify RAL# for custom colors. satin black canopy standard on wood finishes.

### emergency

if required, recommend use of inverter (by other).



## catalog number

--	--	--	--	--

### size

- C4036\*** driver in j-box
- C4036.BABA\*** driver in j-box
- C4036.LV\*** remote enclosure  
2"sq X 36.25"ht
  
- C4048\*** driver in j-box
- C4048.BABA\*** driver in j-box
- C4048.LV\*** remote enclosure
- P4048.LV.BABA\*** remote enclosure  
2"sq X 48.25"ht

\*extended lead time

### beam

- S** 12° spot
- M** 25° med
- W** 38° wide

**jewel**  
see page 6

### CCT

- 27** 2700K
- 30** 3000K
- 35** 3500K
- 40** 4000K

### lumens

- L1** 360 lm
- L2** 630 lm
- L3** 900 lm
- H1** 1265 lm
- H2** 1805 lm

### painted finish

- AP** anodized paint
- BS** brass
- BU** blue
- BZ** bronze
- CP** champagne
- FB** flat black
- GM** gun metal
- MB** military blue
- MW** matte white
- OR** orange
- RD** red
- SB** satin black
- SS** satin silver
- TG** textured gray
- YO** yellow

### premium finish

**RAL** specify RAL#

### wood finish

- ASH** ashwood
  - ENG** english brown oak
  - ESP** espresso
- satin black canopy standard on wood finishes







remote enclosure

This product meets the guidelines for the Build America, Buy America Act. **Some Exclusions Apply.** For more information and full list of eligible SKUs, please contact the factory at [info@impactitg.com](mailto:info@impactitg.com)

[www.impactitg.com](http://www.impactitg.com) / 314-427-1212 / saint louis, mo



specifications subject to change © 2026 rev. 01/27/2026



# Calculation Table

Consult factory for applications assistance




Cat No	Delivered* Lumens	Watts 120V / 277V	IES File #	LLF to be applied
<b>L1</b>	360	3	<b>07222C</b> spot	.30
			<b>07222B</b> med	.30
			<b>07222A</b> wide	.30
<b>L2</b>	630	6	<b>07222C</b> spot	.53
			<b>07222B</b> med	.53
			<b>07222A</b> wide	.53
<b>L3</b>	900	9	<b>07222C</b> spot	.76
			<b>07222B</b> med	.76
			<b>07222A</b> wide	.76
<b>H1</b>	1265	13	<b>07222C</b> spot	1.07
			<b>07222B</b> med	1.07
			<b>07222A</b> wide	1.07
<b>H2</b>	1805	19	<b>07222C</b> spot	1.52
			<b>07222B</b> med	1.52
			<b>07222A</b> wide	1.52


\*delivered lumens based on 4000K, 90+ cri

The application of a Light Loss Factor is required to:


- match the lumen output for the power module specified
- incorporate the increased lumen output due to LED/Driver upgrades



**07222C**  
P40xx-S-40H1  
S 12° spot



**07222B**  
P40xx-M-40H1  
M 25° med



**07222A**  
P40xx-W-40H1  
W 38° wide

job name:   
 type:

## sq.too™ ceiling with jewel spec sheet 90CRI

**material**  
 2"dia smooth extruded aluminum outer housing in six lengths. satin black canopy standard on wood finishes.

**LED**  
 COB in 2700K, 3000K, 3500K, or 4000K 90+ cri standard rated >36,000 hours L70 (6.8K) per LM-80 test data, and 71,000 hours projected life per IES TM-21.

**jewel**  
 3D printed with filament. available in black, frost, and blue.

**driver**  
 constant current, class P, class 2 power unit, class A sound rating, universal input (120-277V) programmable driver, 5% minimum dimming level, PF >0.90. protections include short circuit, input/output isolation and surge protection (3KV). wired for 0-10v dimming from factory.

**mounting standard**  
 driver in junction box (requires 2 1/8" deep electrical box). 5" dia canopy painted to match fixture. satin black canopy standard on wood finishes.

**canopy mounted driver (CDVR)** (optional)  
 2"dia x 6"h extruded aluminum driver housing on 5" dia canopy painted to match fixture.

**remote enclosure (.LV)** (optional)  
 the standard driver can be remote mounted up to 33ft from the LED. remote enclosure supplied. for distances greater than 33ft consult factory. for Chicago Plenum installation consult factory.

**finish**  
 select from 15 standard powder coat paint finishes or 3 wood finishes (listed below) or specify RAL# for custom colors. satin black canopy standard on wood finishes.

**emergency**  
 if required, recommend use of inverter (by other).



## catalog number

--	--	--	--	--	--

size	jewel	length	CCT	lumens	finished
<b>C4006</b> driver in j-box	<b>DBK</b> black	<b>2 2"</b>	<b>27</b> 2700K	<b>L1</b>	<b>AP</b> anodized paint
<b>C4006.BABA</b> driver in j-box	diamond				<b>BS</b> brass
<b>C4006.LV</b> remote enclosure 2"sq X 6"ht	<b>PFR</b> frost pinstripe		<b>30</b> 3000K	<b>L2</b>	<b>BU</b> blue
<b>C4012</b> driver in j-box	<b>KBL</b> blue knurled		<b>35</b> 3500K	<b>L3</b>	<b>BZ</b> bronze
<b>C4012.BABA</b> driver in j-box			<b>40</b> 4000K	contact factory	<b>CP</b> champagne
<b>C4012.LV</b> remote enclosure 2"sq X 12"ht					<b>FB</b> flat black
<b>C4018</b> driver in j-box					<b>GM</b> gun metal
<b>C4018.BABA</b> driver in j-box					<b>MB</b> military blue
<b>C4018.LV</b> remote enclosure 2"sq X 18"ht					<b>MW</b> matte white
<b>C4024</b> driver in j-box					<b>OR</b> orange
<b>C4024.BABA</b> driver in j-box					<b>RD</b> red
<b>C4024.LV</b> remote enclosure					<b>SB</b> satin black
<b>C4024.LV.BABA*</b> remote enclosure 2"sq X 24"ht					<b>SS</b> satin silver
<b>C4036*</b> driver in j-box					<b>TG</b> textured gray
<b>C4036.BABA*</b> driver in j-box					<b>YO</b> yellow
<b>C4036.LV*</b> remote enclosure					
<b>C4036.LV.BABA*</b> remote enclosure 2"sq X 36"ht					
<b>C4048*</b> driver in j-box					
<b>C4048.BABA*</b> driver in j-box					
<b>C4048.LV*</b> remote enclosure					
<b>C4048.LV.BABA*</b> remote enclosure 2"sq X 24"ht					



\*extended lead time


**premium finish**  
 RAL specify RAL#

**wood finish**  
**ASH** ashwood  
**ENG** english brown oak  
**ESP** espresso  
 satin black canopy standard on wood finishes



This product meets the guidelines for the Build America, Buy America Act. Some Exclusions Apply. For more information and full list of eligible SKUs, please contact the factory at info@impactItg.com

## Powder Coat Paint Finishes



**MW** matte white




**AP** anodized paint



**SS** satin silver



**TG** textured gray



**FB** flat black



**SB** satin black



**CP** champagne



**BZ** bronze



**GM** gun metal



**OR** orange 2011



**BU** blue 5017



**BS** brass



**RD** red 3020



**YO** yellow 1018



**MB** military blue

## Premium Finishes\*

### Wood Finishes



**ASH** ashwood



**ENG** english brown oak



**ESP** espresso

For accurate color verification, actual finish samples are available upon request.



**RAL#**

\*Available on select series. Consult product submittal for availability.

